



**OFFICE OF THE REGISTRAR**  
**MAHAPURUSHA SRIMANTA SANKARADEVA VISWAVIDYALAYA**

[Established under the Assam Act No. XIX of 2013]

HALADHAR BHUYAN PATH, KALONGPAR, NAGAON, PIN-782001: ASSAM: INDIA

e-mail: [mssvnagaon@gmail.com](mailto:mssvnagaon@gmail.com), [registrarmssv@gmail.com](mailto:registrarmssv@gmail.com)

website : [www.mssv.co.in](http://www.mssv.co.in) Phone No. : 9531089105, 03672-231146

Ref. No.: MSSV/R/59/2015/

Date: 10.08.2018

**NOTICE INVITING QUOTATION FOR WORKS**

Sealed quotations are invited from the competent and eligible firms/ parties **for fitting charges of floor tiles, wall tiles, Antiskid tiles. Ceramic tiles, etc.** of the Administrative-cum-Academic building at Mahapurusha Srimanta Sankaradeva Viswavidyalaya, Kalongpar, Nagaon as per the required specifications which can be obtained from the Office of the undersigned during office hours.

The **sealed quotations** must reach the office of the undersigned **on or before 16<sup>th</sup> August, 2018**. The party has to pay **an amount of Rs. 1,000.00 (Rupees one thousand) only in cash to Accounts Branch of the University and submit copy of the receipt alongwith the quotation**. The firms/parties shall submit proof of GST Registration, PAN/TIN.

The undersigned reserves the right to accept or reject any quotation without notice.

Sd/-  
(Dr. D. Thakuria)  
Registrar (i/c),  
MSSV, Nagaon  
Date: 10.08.2018

Memo No: MSSV/R/59/2015/**10479-83**

Copy to:

1. The Hon'ble Vice-Chancellor, MSSV, Nagaon for kind information.
2. Dr. Santanu Kalita, Asstt. Professor & Head (i/c), Deptt. of Computer Application, MSSV, Nagaon with a request to upload the notification in the University website **[www.mssv.co.in](http://www.mssv.co.in)**.
3. The Accounts Officer, MSSV, Nagaon for information and necessary action.
4. The Project Technical Assistant (P.T.A.), MSSV, Nagaon for information and necessary action.
5. Notice Board.
6. Office file.

(Dr. D. Thakuria)  
Registrar (i/c),  
MSSV, Nagaon

**NAME OF WORKS: CONSTRUCTION OF ACADEMIC BUILDING AT KALONGPAR, NAGAON (MSSV).**

*Fitting Charges of wall tiles, floor tile, marble stone, Antiskid tiles, Ceramic tiles, etc.*

*Ground floor, First floor, Second floor and Third floor of Academic Building of MSSV, Kalongpar, Nagaon.*

| <b>WALLS</b>               |   | <b>Unit</b> | <b>Rate</b> | <b>Remarks</b> |
|----------------------------|---|-------------|-------------|----------------|
| <u>Sl.No.1</u><br>5.7.1.2  | Providing polished <b>ceramic wall tiles</b> of approved quality, size, shape and thickness not less than 8mm on walls and skirting over cement mortar bed 10mm thick in prop. 1:3 (1 cement : 3 coarse sand) including cutting where necessary finished with flush pointing with necessary finished with flush pointing with Fix-A-Tile (Choksy/Sika/Pedelite/Rouf/white cement slurry) mixed with approved pigment to match shade of tiles complete at all levels as specified and directed. (Cement plastering to be measured and paid separately). (Coloured pigment should be in conformity with colour of tiles and as approved and directed by the Department). (Walls means both interior and exterior walls).<br><b>(a) Delux range Somany/Orient/Nitco/Varmora Make</b><br>(i) Of size 300mm x 450mm and above. | Sq. M.      |             |                |
| <b>FLOOR</b>               |   | <b>Unit</b> | <b>Rate</b> | <b>Remarks</b> |
| <u>Sl.No. 2</u><br>5.7.2.1 | Providing VITRIFIED floor tiles of proved quality of specified size, shape and thickness not less than 18mm on floors, skirtings, risers and treads of steps over 15mm thick base of cement mortar in prop. 1:3 (1 cement : 3 coarse sand) Including cutting where necessary finished with flush pointing with FIX-A-Tile (Choksey/Sika/Pedelite/Rouf) / white cement slurry mixed with approved pigment to match the shade of the tiles, complete at all levels as specified and directed. (Coloured pigment should be in conformity with colour of tiles and as approved and directed by the Department).<br><b>(b) Executive Range (Somany Varmora/ Orient make)</b><br>(i) Of size 800mm x 800mm  | Sq. M.      |             |                |
| <b>PAVERS</b>              |   | <b>Unit</b> | <b>Rate</b> | <b>Remarks</b> |
| <u>Sl.No. 3</u><br>5.7.3.4 | Providing SUN ROCK HIGH CTS/ DEVI paver block/tiles of concrete grade M30 or above of approved quality, size, shape of specified thickness over a levelling bedding layer of 30mm compacted sand over a base course of WBM or PCC (Base course to be paid separately) including cutting where necessary finished with spreading sweeping jointing sand and compacting the pavers using vibrating compactor as specified and directed.<br>(b) 60mm thick.  | Sq. M.      |             |                |
| <b>MARBLE FLOORING</b>     |   | <b>Unit</b> | <b>Rate</b> | <b>Remarks</b> |
| <u>Sl.No. 4</u><br>5.9.2   | 18mm thick marble stone tiles in flooring including risers and treads of steps, skirting, dado walls, pillars laid with 10mm thick base of cement plaster in prop. 1:3 (1 cement : 3 coarse sand) and jointed with grey cement slurry including rubbing and polishing complete with marble tiles of specified quality and shade at all levels. 18mm thick marble stone tiles in flooring including risers and treads of steps, skirting, dado, walls, pillars laid with 10mm thick base of cement plaster in prop. 1:3 (1 cement : 3 coarse sand) and jointed with grey slurry including rubbing and polishing complete with marble tiles of specified quality and shade at all levels.<br>(iv) Rajnagar Marble   | Sq. M.      |             |                |

| <b>GRANITE FLOORING</b>   |  | <b>Unit</b> | <b>Rate</b> | <b>Remarks</b> |
|---------------------------|--|-------------|-------------|----------------|
| <u>Sl.No. 5</u><br>5.10.5 | <p>Providing polished granite slab of approved quality, size, shape and thickness not less than 18mm on floors, skirtings, treads and risers of steps over cement mortar bed 15mm thick in prop. 1: 3 (1cement : 3 coarse sand) including cutting where necessary finished with flush pointing with Fix-A-Tile (Choksey/Sika/ Pedelite/Rouf)/ white cement slurry mixed with approved pigment tom match the shade of granite slab, complete at all levels as specified and directed. (Cement plastering to be measured and paid separately). (Coloured pigment should be in conformity with colour of slab and as approved and directed by the Department).</p> <p><b>(i) Executive Quality</b><br/>(i) With Fix-A-Tile (Choksey/Sika/Pedelite/Rouf)</p> | Sq. M.      |             |                |
| <b>ANTISKID TILES</b>     |  | <b>Unit</b> | <b>Rate</b> | <b>Remarks</b> |
| <u>Sl.No. 6</u><br>5.11.1 | <p>Providing Antiskid Tiles of approved quality, size, shape and thickness not less than 8mm on floor, skirting over a cement mortar bed of 15mm thick in prop. 1:3 (1 cement : 3 coarse sand) approved make fix with Fix-A-Tile ( Choksey/Sika/Pedelite/Rouf)/ white cement complete at all level specified and directed.</p> <p><b>(A) CERAMIC</b><br/>i) <b>Normal range (sizes 300mm x 300mm and above)</b><br/>(a) Orient made: Galaxy Brown, Galaxy creama, Galaxy Pink, Galaxy Green, Pulsar Beige, Pulsar Blue, Pulsar Dove, Pulsar Pink, Burj Brown, Bruj Green, Bruj Slate.</p>  | Sq. M.      |             |                |